



## ***Gazpromneft ATF DX III***

### ***Oil for automatic gear boxes***

#### **DESCRIPTION**

High-quality automatic transmission fluid on a semi-synthetic basis with a special additive package. Intended for automatic gear boxes, transmissions, steering boosters of utility cars, trucks, buses and off-road vehicles in which DEXRON III G fluid type is recommended.

#### **BENEFITS**

- Optimum frictional properties ensure smooth gear shift and work without vibration
- High anti-wear and anti-corrosion properties significantly prolong the transmission service life
- Compatible with the gasket and seal materials used in modern equipment
- Good anti-foaming properties
- Good low-temperature pumping ability

#### **APPLICATION**

- Intended for use in fixed-ratio automatic transmissions with torque convertor, which require fluids meeting specifications Dexron IIIG, IID.
- Applicable for use in automatic gearboxes of ZF, Voith and other producers according to the list of specifications
- In steering boosters of utility in which ATF fluid class is recommended

#### **SPECIFICATIONS AND APPROVALS**

**Gazpromneft ATF DX III is meeting requirements of the following specifications:**

- DEXRON IIIG
- MERCON
- ZF TE-ML 02F, 03D, 04D, 05L, 09, 11B, 14A, 17C, 21L
- Voith H55.6335
- MAN 339 Typ. Z1/V1
- MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.11
- Volvo CE 97340,97341
- Alison C-4
- GM TASA
- Cat TO-2



## PHYSICAL AND CHEMICAL CHARACTERISTICS

<i>TYPICAL PROPERTIES</i>	<i>Gazpromneft ATF DX III</i>
Kinematic viscosity @ 100 °C, mm <sup>2</sup> /s	7,24
Brookfield viscosity @ - 40 <sup>0</sup> C	16 000
Pour point, °C	- 48
Flash point, COC, °C	213
Density @ 20 °C, gr/sm <sup>3</sup>	0,856

## HEALTH AND SAFETY

Gazpromneft ATF DX III oil poses no threat to human health and the environment under keeping of service rules of personal and industrial hygiene, as well as when used properly in the recommended applications. Avoid contact with skin. When changing the oil, use protective gloves/mittens. Upon skin contact, wash the oil off with the soap and water immediately. For more information on this subject please refer to the product safety data sheet.

## ENVIRONMENTAL PROTECTION

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.