

Gazpromneft Hydraulic HVLP

Hydraulic Oils



Hydraulic systems



Wide range of operating temperatures



High anti-wear properties



Excellent filterability



High quality mineral base oils

Gazpromneft Hydraulic HVLP oils are premium high performance anti-wear hydraulic oils designed to satisfy a wide range of hydraulic equipment requirements. Formulated with high-quality mineral base oils and selected additives they provide very good anti-wear properties, rust and corrosion protection, oxidation resistance and antifoam properties. The high viscosity indexes provide excellent low and high temperature properties for equipment that is subjected to a wide range of start-up and operating temperatures.. They are designed for systems operating under moderate conditions where high levels of anti-wear protection are needed.

Applications

- Wide variety of industrial and mobile applications
- Hydraulic systems requiring anti-wear oils
- Systems containing gears and bearings requiring mild anti-wear properties
- Systems where low start-up and high operating temperatures are typical, including outdoor applications
- Hydraulic pumps by wide range of manufacturers, including Denison, Cincinnati Machine, Eaton Vickers, Bosch Rexroth.

Features, Advantages & Potential Benefits

- **High viscosity index and good shear stability**
Maintain excellent viscosity characteristics for long periods of time for long equipment life
- **Low pour points**
Good fluidity conditions at low temperatures provide good pumpability at low temperatures
- **Very good foam control**
High performance and smooth hydraulic operations
- **Exceptional corrosion protection**
Reduces the negative effects of moisture on system components
- **Effective oxidation and thermal stability**
Reduce deposits and improve valve performance
- **Excellent anti-wear properties**
Proven zinc-based additives help to reduce wear and protects pumps and components for extended equipment life
- **Ultra Keep Clean Performance**
Reduced system deposits leading to reduced machine maintenance and increased component life

Approvals & Specifications

	Gazpromneft Hydraulic HVL					
	10	15	22	32	46	68
Meet the requirements of:						
DIN 51524 Part 3	✓	✓	✓	✓	✓	✓
Bosch Rexroth RDE 90235				✓	✓	
Builder approvals:						
Denison HF-0,1,2				✓	✓	✓
Fives Cincinnati				P-68	P-70	P-69
Eaton Vickers 35VQ25		meet	meet	✓	✓	✓
Bosch Rexroth 90220-01			meet			✓

Typical Characteristics

Properties	Method	Gazpromneft Hydraulic HVL					
		10	15	22	32	46	68
ISO Viscosity Grade		10	15	22	32	46	68
Kinematic Viscosity @40°C, mm ² /s	ASTM D 445	10	15	22	32	46	68
Kinematic Viscosity @100°C, mm ² /s	ASTM D 445	3,0	4,0	4,9	6,4	7,9	10,5
Kinematic Viscosity, mm ² /s	ASTM D 445	1100 @-40°C	600 @-30°C	700 @-20°C	1200 @-20°C	1100 @10°C	-
Viscosity Index	ASTM D 2270	170	170	155	160	142	141
Flash Point (COC), °C	ASTM D 92	175	160	196	218	226	230
Pour Point, °C	ASTM D 97	-60	-58	-50	-46	-40	-38
Cleanliness class, max	ISO 4406	-/17/14	-/17/14	-/17/14	-/17/14	-/17/14	-/17/14
Density @20°C, kg/m ³	ASTM D 4052	820	840	865	870	880	880

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.